- (4) Identification of resources to be provided by the certificate holder for implementation of the plan.
- (5) Procedures to be followed during air carrier operations, including at least—
- (i) Assignment of personnel responsibilities for implementing the procedures:
- (ii) Conduct of physical inspections of the movement area and other areas critical to wildlife hazard management sufficiently in advance of air carrier operations to allow time for wildlife controls to be effective;
 - (iii) Wildlife control measures; and
- (iv) Communication between the wildlife control personnel and any air traffic control tower in operation at the airport.
- (6) Periodic evaluation and review of the wildlife hazard management plan for—
- (i) Effectiveness in dealing with the wildlife hazard; and
- (ii) Indications that the existence of the wildlife hazard, as previously described in the ecological study, should be reevaluated.
- (7) A training program to provide airport personnel with the knowledge and skills needed to carry out the wildlife hazard management plan required by paragraph (d) of this section.
- (f) Notwithstanding the other requirements of this section, each certificate holder shall take immediate measures to alleviate wildlife hazards whenever they are detected.
- (g) FAA Advisory Circulars in the 150 series contain standards and procedures for wildlife hazard management at airports which are acceptable to the Administrator.

§139.339 Airport condition reporting.

- (a) Each certificate holder shall provide for the collection and dissemination of airport condition information to air carriers.
- (b) In complying with paragraph (a) of this section, the certificate holder shall utilize the NOTAM system and, as appropriate, other systems and procedures acceptable to the Administrator.
- (c) In complying with paragraph (a) of this section, the certificate holder shall provide information on the fol-

lowing airport conditions which may affect the safe operations of air carriers:

- (1) Construction or maintenance activity on movement areas, safety areas, or loading ramps and parking areas.
- (2) Surface irregularities on movement areas or loading ramps and parking areas.
- (3) Snow, ice, slush, or water on the movement area or loading ramps and parking areas.
- (4) Snow piled or drifted on or near movement areas contrary to §139.313.
- (5) Objects on the movement area or safety areas contrary to §139.309.
- (6) Malfunction of any lighting system required by § 139.311.
- (7) Unresolved wildlife hazards as identified in accordance with §139.337.
- (8) Nonavailability of any rescue and firefighting capability required in §§ 139.317 and 139.319.
- (9) Any other condition as specified in the airport certification manual or airport certification specifications, or which may otherwise adversely affect the safe operations of air carriers.
- (d) FAA Advisory Circulars in the 150 series contain standards and procedures for using the NOTAM system for dissemination of airport information which are acceptable to the Administrator.

[Doc. No. 24812, 52 FR 44282, Nov. 18, 1987; 53 FR 4258, Feb. 12, 1988]

§ 139.341 Identifying, marking, and reporting construction and other unserviceable areas.

- (a) Each certificate holder shall—
- (1) Mark and, if appropriate, light in a manner acceptable to the Administrator—
- (i) Each construction area and unserviceable area which is on or adjacent to any movement area or any other area of the airport on which air carrier aircraft may be operated;
- (ii) Each item of construction equipment and each construction roadway, which may affect the safe movement of aircraft on the airport; and
- (iii) Any area adjacent to a navaid that, if traversed, could cause derogation of the signal or the failure of the navaid, and

§ 139.343

- (2) Provide procedures, such as a review of all appropriate utility plans prior to construction, for avoiding damage to existing utilities, cables, wires, conduits, pipelines, or other underground facilities.
- (b) FAA Advisory Circulars in the 150 series contain standards and procedures for identifying and marking construction areas which are acceptable to the Administrator.

§139.343 Noncomplying conditions.

Unless otherwise authorized by the Administrator, whenever the requirements of subpart D of this part cannot be met to the extent that uncorrected unsafe conditions exist on the airport, the certificate holder shall limit air carrier operations to those portions of the airport not rendered unsafe by those conditions.